

ROLL-X® Multipurpose Applicator 400/175 PROFESSIONAL



MODEL NAME	ROLL-X® 400/175 Professional
Model type	Professional
Part no.	10535
Bed length	4 000 mm / 13ft. 1in.
Bed width	1 750 mm / 5ft. 9in.
Length of working area	3 600 mm / 11ft. 9in.
Width of working area/roller width	1 650 mm / 5ft. 5in.
Overall width incl. Glide beam	1 940 mm / 6ft. 4in.
Max. thickness of substrate	85 mm / 3 2/5in.
Work height flatbed	750-1 110 mm / 2ft. 5in - 3ft. 7in.
Bed surface	Tempered glass + Cutting mat
Power Supply	230V/50Hz (10A) / 120V/60Hz 15A)
Required air pressure	6-8 bar / 87-116 psi
Weight	650 kg / 1433 lb
Packing weight, total	850 kg / 1874 lb
Packing dimension, delivered in parts	4 100 x 710 x 2 100 mm / 13ft 5in. x 2ft. 4in. x 6ft. 10in.
Packing dimension, delivered assembled	4 100 x 2 000 x 1 600 mm / 13ft 5 in. x 6ft 7in. x 5ft 3in.
Wheels	4
Warranty	2 years
Owner's Manual	yes (en)
Roll holder for Glide Beam	yes
Roll holder for bed end	yes
Side trays, adjustable	yes
Roll cradle, 1300mm / 4ft 3in.	yes
Light table (LED)	yes
Electrical height adjustment	yes
Long life compressor	option
Assembled when delivered	option

KEY FEATURES

- Electrical height adjustment 750-1 110 mm / 2ft. 5in - 3ft. 7in.
- Adjustable side trays
- Metal side lines used for trimming
- Fast assembly and installation

ROLL-X Professional is the fully equipped multipurpose work table that gives you access to the superior production method provided by the Flatbed Applicator technique. The machine can either be shipped in modules to reduce shipping cost and gives you the possibility to fit through a standard door, or be delivered fully assembled. The assembling is fast and easy and you will start making money in no time! ROLL-X Pro is equipped LED and electrical height adjustment.



ROLL-X
MULTIPURPOSE APPLICATOR

info@roll-x.se
roll-x.se
+46 54 770 70 00